

DUOSCREED-E

Rev. 0/30-09-2015

MACHINE FOR COMPACTING AND LEVELLING OF FLOORS

A multifunctional machine that can be used as vibrating beam and wet screed.

Description

DuoScreed combines a vibrating beam and wet screed in one machine. This electric powered version is derived from the patented machine (Nr 1010349) consists of a driving unit and a blade system which enables changing blades of various widths. The drive unit only weighs 12 kg and is provided with 230V 50Hz 1-Phase 350W double isolated electric motor.



Characteristics

The main characteristics of DuoScreed are:

- Easy to transport thanks to supply in 2 components.
- The power unit is equipped with a quick connecting system, which allows attachment of various blade widths within a minute (no tools required).
- Specially designed end caps on each side of the blades prevent stripes and ridges on the surface.
- Twin handle design, easy to adjust and can be folded down for transport or storage.
- The power unit can easily be rotated 180° to allow the operator to screed on forms/rails or for change to wet screeding.
- Equipped with motor speed regulator for vibration control

Technical information

TYPES LW BLADES	TYPE ENGINE	WEIGHT
		Engine --- Blade
m		
WORKING WIDTH LW 1.52	230V 50HZ 350W 1Phase	12 kg --- 5.3 kg
WORKING WIDTH LW 1.83	230V 50HZ 350W 1Phase	12 kg --- 6.4 kg
WORKING WIDTH LW 2.44	230V 50HZ 350W 1Phase	12 kg --- 8.5 kg
WORKING WIDTH LW 3.05	230V 50HZ 350W 1Phase	12 kg --- 10.1 kg